

MAINTENANCE, REPAIR AND REPLACEMENT STANDARDS POLICY

Draft Template Policy For Associations Consideration

with access to the Unit for dryer vent fro cleaning. **To be completed between July 1st and September 30th annually or in odd numbered years.**

3. Water Heater Replacement - (If applicable)

Water heaters must be replaced within a ten year period. Any damage caused by a malfunctioning water heater past the age of ten years that is not covered by the Master Insurance Policy will be the responsibility of the unit owner whose unit is served by the heater. OR In the event any loss, claim, damage or expense is caused or contributed to by water which escapes from any water heater located within the boundaries of a Unit, there shall be a rebuttable presumption that the water heater failed because it was not replaced prior to the expiration of its anticipated useful life. The aforesaid presumption may be rebutted by the Unit Owner by providing proof to the Association satisfactory to the Association that the water in question had not exceeded its anticipated life.

4. Washing Machines - (If applicable)

All washing machines must have reinforced steel/metal braided hoses designed to prevent or greatly reduce the potential for hose failure and resulting water damage.

5. Toilets and Plumbing - (If applicable)

No running water spigots may be left unattended or allowed to cause overflow. Outdoor spigots must be winterized to prevent freezing. All leaky pipes, valves, toilet seals, toilet gaskets and running toilets must be promptly repaired. Evidence of running or seeping water must be reported immediately to the Association's Management Company. Each unit owner shall be responsible to report evidence of Mold or conditions that could lead to Mold to the Association's Management Company.

6. Reporting Leaks

Unit owners shall promptly report to the Association any leak or other condition resulting in escaped water upon identifying any such leak or condition or as quickly thereafter as is reasonably possible.

7. HVAC Maintenance - - (If applicable)

HVAC units must have a full annual inspection performed by a licensed technician. Inspection shall include the systems, vents, flues used for venting combustion gases or supplying combustion air. All repairs, cleaning, and maintenance must be completed at the time of inspection. Unit owners are required to maintain receipt records from contractors verifying that the required HVAC inspection and cleaning has occurred. **To be completed between March 1st and June 30th**

8. Smoke Detectors

Smoke detectors are to be tested in January and July each year. Batteries must be replaced annually in January. It is the responsibility of the owner to ensure that any and all smoke detectors found to not be in working order are replaced with the appropriate device (verify if device is 110 volt hardwired

It is important to note that standards outlined within the "Community Association Maintenance Standard" template are offered as draft guidelines. Your actual guideline standards will differ based on the boards specific evaluation of your community. This list has attempted to account for the different possibilities that a community may need to consider for the purposes of developing this policy. Each association should carefully review any proposed maintenance standards against current practices and loss run history in your community.

MAINTENANCE, REPAIR AND REPLACEMENT STANDARDS POLICY

Draft Template Policy For Associations Consideration

with 9 volt battery back up and whether interconnected with other smoke detector devices within the unit or building). **To be completed in January and July**

9. Heat in Units

Each Unit Owner shall be responsible to continuously maintain heat at no less than 65 degrees Fahrenheit in all areas contained within the boundaries of the Unit. In case of the unit being unoccupied, the unit owner must provide the management company with a local emergency contact. The emergency contact must inspect the vacant unit at least once per week to check for proper functioning of the heating system, frozen pipes, water leaks, or any other issues that may arise in the resident's absence.

10. Outside Spigots

If the shut off for the spigot is inside the unit, the owner must shut off the water and properly winterize the spigot by December 1st. Water may be turned on after April 15th. Valves replaced shall be replaced using a "frost free valve".

11. Grill Safety

The use of charcoal or solid fuel grills is prohibited. Each unit owner having a gas fueled grill needs to ensure that it is in safe working condition and is operated safely not limited to: providing adequate space between the exterior surfaces of the grills and adjacent surfaces; no propane containers larger than 1 pound be stored within any structure, and that gas supply to the grill be in the closed position when the grill is not being used.

12. Work to be Performed by Licensed Professionals

Each unit owner shall be responsible to the Association for any damage caused by repairs or installations to any unit or limited common element not performed by licensed and insured professionals in accordance to at least the minimum standards required by the State of Connecticut and the municipality in which the unit is located.

13. Reporting Association Required Maintenance

The unit owner is responsible for reporting maintenance problems to management in a timely fashion and, if required, must provide reasonable access to the unit for inspection and/or repairs as needed.

14. General Requirements

- a. There shall be no storage of combustibles or hazardous materials (including but not limited to paints, thinners, gasoline, propane tanks, etc.) inside units, garages, or other enclosed spaces.
- b. Unit owners are responsible for notifying all residents of their unit of these rules and guidelines. Compliance with the maintenance standards outlined herein is the responsibility of the unit owner. For the purpose of interpreting and applying these maintenance, repair standards, where the context requires, the term "unit owner" shall also include any tenant, guest, invitee or other occupant of the unit.

It is important to note that standards outlined within the "Community Association Maintenance Standard" template are offered as draft guidelines. Your actual guideline standards will differ based on the boards specific evaluation of your community. This list has attempted to account for the different possibilities that a community may need to consider for the purposes of developing this policy. Each association should carefully review any proposed maintenance standards against current practices and loss run history in your community.

MAINTENANCE, REPAIR AND REPLACEMENT STANDARDS POLICY

Draft Template Policy For Associations Consideration

- c. All maintenance, inspections, and repairs to units must be done by licensed and insured contractors. The contractor must obtain permits for work where required by the municipality.
- d. The unit owner should retain a copy of any documentation related to the completion of the above maintenance requirements in the event that documentation of compliance is requested by the Association.

14. Optional Maintenance Considerations

- a. **Electrical Panels:** Regular inspection of wiring and breakers should be conducted. An electrician must replace any old, worn, or damaged breakers and wiring. Total electrical usage both in the aggregate and per circuit in any Unit shall not exceed the capacity of the circuits which serve the Unit as labeled on or in the circuit boxes. Electrical breakers shall not be connected to more than one electrical conductor.
- b. **Hot Water Tanks:** Installation of an automatic shut off device should be considered to minimize damage should the water heater fail. Where feasible, installation of water heater pan with appropriate drainage pipe should be considered. If drain connects to any common piping or travels beyond the boundaries of the unit, an approved variance request is required.
- c. **Doors/Windows/Garage Doors:** The owner must properly maintain these items by repairing or replacing as needed. The owner shall ensure that all windows and doors are properly closed and latched to prevent damage from precipitation or wind blown precipitation.

DRAFT

It is important to note that standards outlined within the "Community Association Maintenance Standard" template are offered as draft guidelines. Your actual guideline standards will differ based on the boards specific evaluation of your community. This list has attempted to account for the different possibilities that a community may need to consider for the purposes of developing this policy. Each association should carefully review any proposed maintenance standards against current practices and loss run history in your community.